SC-DM-XX SERIES ZONE CONTROL DAMPER SPECIFICATIONS

APPLICATION:

SC-DM-XX zone control dampers include a damper and two-position 24V power close/power open, 3-wire actuator and can be used with residential and commercial zone control systems. The dampers can be installed in any position and are rated for duct systems having less than 1.0" WC.


AVAILABLE SIZES:

Diameters: 6", 8", 10", 12", 14", 16", 18", 20"

Length: 10"

CONSTRUCTION:

Shell Material: 18 gauge steel
Damper Material: 18 gauge
Shaft: 18 gauge
½"aluminum



DAMPER SIZE	"A" DIMENSION
6"	10"
8"	10"
10"	10"
12"	10"
14"	10"
16"	10"
18"	10"
20"	10"

AIR FLOW & PRESSURE:

Max static pressure: 1.0" WC
Max velocity: 2,000 fpm
CFM: 0-4,000 cfm

DAMPER ACTUATOR:

24VAC, 2.5VA, 3-wire floating point actuator, 60 second timing Torque 18 in-lb




COMPONENTS:

Damper and actuator

WARRANTY:

Damper: 5 Years



Drawings are intended to show general, overall product dimensions and provide guidance for installation clearance. Drawings are not to scale. Specified Controls reserves the right to make product changes without notification or obligation.



5351 E. Thompson Road Box 128 Indianapolis, IN 46237 www.specifiedcontrols.com Phone: 888.359.0365